

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/054633 A1

(51) International Patent Classification⁷: F01D 17/16, 5/14

Giuseppe [IT/IT]; Via della Quercia 18/B, I-50019 Sesto Fiorentino (IT).

(21) International Application Number:
PCT/EP2004/013657

(74) Agents: COPPO, Alessandro et al.; Ing. Barzanò & Zannardo Milano S.p.A., Via Borgonuovo, 10, I-20121 Milan (IT).

(22) International Filing Date:
30 November 2004 (30.11.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI2003A002388 5 December 2003 (05.12.2003) IT

(71) Applicant (for all designated States except US): NUOVO PIGNONE HOLDING S.p.A. [IT/IT]; Via F. Matteucci, 2, I-50127 Firenze (IT).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

(72) Inventor; and

(75) Inventor/Applicant (for US only): SASSANELLI,

[Continued on next page]

(54) Title: VARIABLE NOZZLE FOR A GAS TURBINE



(57) Abstract: Variable nozzle (10) for a gas turbine fixed to a shaft (11) equipped with a pressurized upper surface (12) and a depressurized lower surface opposite to the upper surface (12), the variable nozzle comprises a series of substantially "C"-shaped sections, each having a first rounded end and a second rounded end each section of the series of sections also having the concavity facing upwards with respect to a base (90) and arranged one after another continuously, in the direction of an axis of the shaft (11) along a curved line (60), the at least second degree curved line (60) lies on a surface (70) having an axis orthogonal to the axis of the shaft (11) and also tilted with respect to the base (90) by an angle (80).

WO 2005/054633 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,
SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*